

Datasheet for torque direct drive ERD08 and servo drive Indradrive Cs
Type of motor: ERD08



Date of creation: 23.10.2018

Description	Symbol	Unit	comment
-------------	--------	------	---------

Electrical data

S-0-0141	Type of axis				
P-0-4014	Type of motor	Torque motor		0200h	
P-0-0512	Temperature sensor			3	
	PWM frequency		kHz	4	
S-0-0111	Motor idle current (eff.)	I_d	A	0,8	
	Nominal motor torque	F_{nenn}	Nm	0,8	with temperature increase of 65 K inside motor
	Power loss	P_{vdauer}	W	18	with temperature increase of 65 K inside motor
S-0-0109	Motor peak current (eff.)	I_{max}	A	2,43	
	Motor peak torque	F_{max}	Nm	2,4	
S-0-0092	Bipolar torque limit value	auf I_d bezogen	%	303,8	
P-0-0109	torque peak limit	auf I_d bezogen	%	303,8	
P-0-0051	Torque/Force constant	k_t	Nm/A	1	
	Motor constant	K_m	Nm/√W	0,2	
	BEMF (speed 600 U/min)	K_e (Phase-Phase)	V	116	
	Thermal resistance	R_{th}	K/W	3,61	temperature increase (65 K) / Plconst
S-0-0113	max. motor speed	U_{max}	U/min	600	
P-0-0018	Number of pol pairs	PPZ		7	
	Type of circuit			Y	
	Nominal intermediate circuit voltage	U_{nom}	V	530	
	Max. intermediate circuit voltage	U_{max}	V	900	
	Inductance	$L_{U-V}, L_{V-W}, L_{W-U}$	mH	22,8	
P-0-4016	Motor series inductance		mH	11,4	
P-0-4017	Motor shunt inductance		mH	11,4	
P-0-4048	Winding resistance by 25°C	$R_{U-V}, R_{V-W}, R_{W-U}$	Ohm	24,3	
	Winding resistance by 90°C	$R_{U-V}, R_{V-W}, R_{W-U}$	Ohm	30,5	
	Electrical time constant		ms	0,9	
	Type of temperature sensor			KTY	
S-0-0201	Motor warning temperature		°C	85	
S-0-0204	Motor shutdown temperature		°C	90	
	Insulation class			F	

Mechanical data

	Mass of motor	kg	1,5	
--	---------------	----	-----	--

Control parameters without mass moment of inertia

S-0-0106	Current loop propotional gain		V/A	22
S-0-0107	Current loop integral action time		ms	0,5
S-0-0104	Position loop KV-Factor	kv		1
P-0-0004	Velocity loop smoothing time const.			500
S-0-0100	Velocity loop propotional gain	kp		0,03
S-0-0101	Velocity loop integral action time	TN		10

Parameter of position

S-0-0277	Position feedback 1 type			1001 b
S-0-0278	Maximum travel range		mm	4000

Encoder Feedback

Motor	ERS	MRDS	ERD	ERI
Sensor designation	LE100	Encoder Kit R	SKM36	SKS90
Manufacturer	SIKO	Numerik	Sick	Sick
Supply voltage	5 V	5V	7-12V	7-12V
Waveform	sin/cos	sin/cos	sin/cos / Hiperface	sin/cos / Hiperface
Reference mark	1	1	--	--
Signal amplitude	1 Vss	1 Vss	1 Vss	1Vss
Feedback revolution	160	2048	128	64

Motor connection

Connector	Connector	Contact
Interconnectron	U	thick 1
Typ: LEAB08AN	V	thick 4
	W	thick 3
	Erde	thick 2
PTC	PTC	thin C
		thin D

Encoder Feedback

	ERS	MRDS	ERD	ERI
	Sub D pin	Sub D pin	Sub D pin	Sub D pin
Signal	Pin	Pin	Pin	Pin
0V Sense				
Ref - / EncData-	6	6	6	6
Ref + / EncData+	5	5	5	5
/B (COS-)	4	4	3	3
B(COS+)	3	3	4	4
A(SIN+)	1	1	2	2
/A(SIN-)	2	2	1	1
N.C.				
GND (0V)	7	7	7	7
N.C.				
Ucc	8	8	8	8
N.C.				
GND (Schirm)				
N.C.				
ID	direct	direct	357798	